



Total Pages

UTILITY PATENT APPLICATION **TRANSMITTAL**

OPT 32U First Named Inventor or Application Identifier

SMALSER, P. J.

Attorney Docket No.

Only for new no	onprovisional applications under 37 CFR 1.53	10)) Express	Mau Label No.	EJ047402687	US H
	PPLICATION ELEMENTS pter 600 concerning utility patent application of	contents.	ADDRESS		
2. Specific (Subtraction of Subtraction of Subtract	e Transmittal Form brit an original, and a duplicate for fee proces ecification [Total Pages] escriptive title of the Invention ross References to Related Applications tatement Regarding Fed sponsored R & eference to Microfiche Appendix ackground of the Invention rief Summary of the Invention rief Description of the Drawings (if filed) etailed Description laim(s) bestract of the Disclosure awing(s) (35 USC 113) [Total Sheets Declaration [Total Pages] Newly executed (original or copy) Copy from a prior application (37 Original for continuation/divisional with Box 17 (Note Box 5 below) i. DELETION OF INVENTOR(s) Signed statement attached inventor(s) named in the prior see 37 CFR 1.63(d)(2) and original or copy) or poration By Reference (useable if Box 4 e entire disclosure of the prior application by of the oath or declaration is supplied considered as being part of the disclosure companying application and is hereby in erence therein.	SED CFR 1.63(d)) completed) d deleting or application, 1.33(b). 4b is checked) on, from which is i under Box 4b, ure of the incorporated by	7. Nucleotide (If applicab. a. b. c. ACCON 8. Ass 9. (wh 10. Eng 11. Info Stat 12. Prei 13. (Sh 14. Smal 15. (Cer (If fo 16. Oth	and/or Amino Acid Sole, all necessary) Computer Readate Paper Copy (identify) Statement verifying IPANYING APPLICATE Signment Papers (covered and assignment of the property of the proper	equence Submission ble Copy tical to computer copy) ing identity of above copies CATION PARTS er sheet & document(s)) int Power of Attorney iment (if applicable) Copies of IDS Citations (MPEP 503) emized) ement filed in prior application, us still proper and desired Document(s)
Cor	ntinuation Divisional . Continu	uation-in-part (Cl	IP) of prior a	application No:	<i></i> `
	18. COF	RESPONDE	NCE ADDRES	S	
☐ Custom	ner Number or Bar Code Label		ach bar coole label h	or D⊅ con	respondence address below
NAME	MICHAEL Y. EPSTEI	N			
ADDRESS	359 GRIGGSTOWN RO)AD			
CITY	BELLE MEAD	STATE	N.J.	ZIP CODE	08502 ·
COUNTRY	USA	TELEPHONE	(908) 359		(908) 359- 1493

Attorney's Docket No Applicant or Patentee: Serial or Patent No.: 0 /	OPT	37	24	
Applicant or Patentee:				
Serial or Patent No.: 0 /				
Filed or Issued:				
For:				
VERIFIED STATEMENT (DECLARATION) CLAIMIN STATUS (37 CFR 1.9(f) and 1.27(c))—SMALL BUSIN				?
hereby declare that I am				
the owner of the small business concern identified belo	ow:			
an official of the small business concern empowered to cern identified below:		on bet	alf of the	con-
NAME OF CONCERN OCEAN POWER TECHNOLOGIE	s, I	NC.	·	
ADDRESS OF CONCERN 1590 REED ROAD, BUIL		Α,	SUITE	1
PENNINGTON, N.J. 0853	4			
coses of paying reduced fees under Section 41(a) and (b) of Title in that the number of employees of the concern, including those exceed 500 persons. For purposes of this statement, (1) the number of section is the average over the previous fiscal year of the employed on a full-time, part-time or temporary basis during each iscal year, and (2) concerns are affiliates of each other when either concern controls or has the power to control the other, or a trols or has the power to control both. The power to the end of the control to the power to control the other, or a trols or has the power to control both.	of its mber one cone con of the ther, of third-p	affilia of emp ocem of e pay directly oarty o	ates, does bloyees of of the pers periods of y or indire or parties	f the sons f the ectly, con-
he small business concern identified above with regard to the inverse protection arrangement for natural energy.	ention,	, entitl	ed	With
by inventor(s) PAUL J. SMALSER, CHARLES B. CARE	ROLL			
described in				
application serial no. 0 /, filed	I			

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention avening to their status as small entities. (37 CFR 1-27).

8437234925

4000ECC		······································
ADDRESS		
INDIVIDUAL	SMALL BUSINESS CONCERN	NONPROFIT ORGANIZATION
NAME		
ADDRESS		
INDIVIDUAL	SMALL BUSINESS CONCERN	NONPROFIT ORGANIZATION
I hereby declare that statements made on statements were ma	information and belief are believed de with the knowledge that willful	own knowledge are true and that all d to be true; and further that these I false statements and the like so
made are punishable United States Code, a	nt issuing thereon, or any patent to	ts may jeopardize the validity of the which this verified statement is di-
made are punishable United States Code, a application, any pater rected.	and that such willful false statement is suing thereon, or any patent to Char-	ts may jeopardize the validity of the which this verified statement is di- les F. Dunleavy
made are punishable United States Code, a application, any pater rected. NAME OF PERSON S	and that such wilful false statement issuing thereon, or any patent to SIGNING	ts may jeopardize the validity of the which this verified statement is di- les F. Dunleavy e President, Finance
made are punishable United States Code, a application, any pater rected. NAME OF PERSON S	and that such wilful false statement issuing thereon, or any patent to SIGNING	ts may jeopardize the validity of the which this verified statement is di- les F. Dunleavy e President, Finance Reed Read
made are punishable United States Code, application, any pater rected. NAME OF PERSON STITLE OF PERSON COMMENTS.	and that such wilful false statement issuing thereon, or any patent to SIGNING	ts may jeopardize the validity of the which this verified statement is di- les F. Dunleavy e President, Finance

Protection Arrangement for Natural Energy Power Generation Systems

This application claims the benefit of provisional patent application 60/105,990 filed October 28, 1998.

Background of the Invention

This invention relates to the generation of electrical power from natural sources of energy, e.g., ocean waves, and particularly to the protection of the power generating system during conditions of excessively high levels of input energy, e.g., during ocean storms, while still operating the system for producing power.

One technique for protecting a power generating system during excessively high levels of input energy is simply to shut the system down; e.g., submerge a floating system normally responsive to the passage of ocean waves sufficiently deeply to be isolated from the surface storm conditions. A problem with this, however, is that power production is lost while the system is shut down.

Solutions are known where the power generating systems are only partially shut down; e.g., a system normally floating freely on the surface of an ocean is submerged beneath the surface but at a depth still responsive to the over-passing waves. Generally, however, such partial shut down solutions are complex and relatively slow operating.

The present invention provides a protection arrangement which is simple, inexpensive and quickly responsive to changing circumstances.

Summary of the Invention

In a power generating system using an electrical generator for generating electrical output power from the system, protection against excessive input energy levels is obtained by increasing the current output from the generator to an amount greater than that would "normally" otherwise be generated at the generator output in response to the increased energy input. The higher than normal output current changes the system operating efficiency and increases the mechanical impedance of the system to a level higher than would be present if the "normal" output current were being generated. The higher system mechanical impedance thus "stiffens" the system against the increased input energy, thus preventing for example, excessively high generator speeds of rotation. The system, while now operating at a less than optimum operating efficiency, continues to generate power.

Description of the Drawing

The sole drawing figure is a schematic illustration of a power generating system in accordance with the invention.

Description of Preferred Embodiments of the Invention

With reference to the drawing, a power generating system is illustrated for converting, by way of one example of use of the invention, energy contained in waves on the surface of an ocean to useful electrical power. Many such systems are known. Herein, quite simply, a float 10 vertically oscillates in response to passing waves for driving a hydraulic cylinder 12 for pressurizing a fluid for driving a hydraulic motor 14 for driving an electrical generator 16 for

generating electrical energy for transfer to an electrical load 18, e.g., an a.c. to d.c. rectifier for charging a storage battery.

Normally, the problem is to maximize the power output from the system, and the system is designed for operation at maximum possible efficiency.

As known, various energy converters, such as ocean wave and wind and water flow energy converters operate most efficiently when they are driving a power generating system whose impedance is matched to the configuration of the energy converter, and to the natural energy level present. The impedance can be thought of as the ratio of the force required to drive a system to the velocity produced in the driven system. A low impedance system will move rapidly when a small force is applied, whereas a high impedance, or stiff, system will move slowly even when a large force is applied. The power delivered to a system is the product of force and velocity (e.g., Newtons times meters per second (Nm/s) equals Watts of power). Drive systems for natural energy sources are normally designed and controlled to produce the maximum product of force and velocity delivered as power from the entire system.

During times of storms or other events, there can be very large amounts of natural energy impinging on a wave or flow energy converter. When this high natural energy is converted to mechanical energy, the system can be damaged or destroyed. For example, a piston with a physically defined stroke can be driven through its end stops, or a turbine can be driven fast enough that it is structurally damaged, or that its attached generator produces voltages that exceed the limits of the generator or its circuitry.

This disclosed innovation prevents system damage due to storms, while still producing power, by adjusting the impedance of the system from the optimum system efficiency values to high levels that impede the production of large

motions or speeds. The technique for system impedance adjustment is to vary the electrical load of the electric power generator. These higher levels of system impedance do not just absorb the natural energy less efficiently, they greatly reduce the conversion efficiency of the natural energy converter. This reduction in natural energy conversion efficiency can easily be a factor of ten. This greatly reduces the level of mechanical energy delivered to the drive system and prevents damage. This disclosed system is intelligent and only reduces the overly high energy available to acceptable levels while continuing to generate useful power.

The electric power generated by an electromagnetic generator is comprised of volts (potential) and amps (current). The product of the voltage times the amperage is the power in Watts (P = VxA). Thus, 100 Watts of power could be comprised of 100 volts times 1 amp, or 1 volt times 100 amps. With electromagnetic generators, the voltage produced is directly related to the generator's speed of rotation. The amount of current that can be produced at that voltage is directly related to the torque applied to the generator's shaft. These properties provide the opportunity for the generator's electronic circuitry to control the generator's mechanical impedance as seen at its drive shaft. As an example, assume a generator is being driven with a shaft speed of 5 Hertz (Hz), and is producing 100 volts while 1 amp is being drawn from the generator by its power circuitry. The generator is producing 100 Watts. The equation for mechanical power in a rotary device is P = 2 Tf, where:

P = mechanical power in Watts

T = the torque applied to the shaft in Nm

f = frequency of shaft rotation in Hz

In this case, 100 = 2 T5, and therefore the torque required at the shaft is at least T = 3.18 Nm. The reason that the term "at least" is used is that a generator

is not 100% efficient in converting torque into electrical current. However, the torque and current are directly related in a particular generator operating under particular conditions, and the principles of operation herein disclosed remain true for all typical generators. Therefore, in the present illustrative example, it is accepted that the torque-to-current coefficient of the generator is T = 3.18 Nm/amp.

In this example, if the power electronics circuit begins to draw 2 amps from the generator, the immediate power produced would be 200 Watts. If the natural energy source is providing sufficient energy, the generator speed can remain at 5 Hz, the torque input will be 6.36 Nm, and the power generated will remain at 200 Watts. This situation is good from an economic point of view, but does not provide over-stroke protection. If the power electronics circuit begins to draw 3 amps from the generator, the immediate power produced would be 300 Watts and the torque required would be T = 3x3.18 = 9.54 Nm. If the natural energy source is not providing sufficient energy to produce this torque, the generator speed cannot remain at 5 Hz. Assume, for example, that the speed decreases to 4 Hz. In this case the power generated would be P = 2 (3x3.18)4 = 240 Watts. More power is being generated and the system has slowed down. Thus, the chance of over stroking or over speeding has been reduced.

Now assume that the power electronics begins to draw 4 amps from the generator, and that this is at the limits of torque or force that the natural energy converter can extract from the environment. In this case, the speed will decrease significantly, for example to 1 Hz. The power generated would be P = 2 (4x3.18)1 = 80 Watts. The actual power delivered may be even lower due to increased heating losses in the generator windings caused by the increased current flow. However, power is still being generated as the system motion is greatly

retarded. Further increases in the current drawn from the generator would increase the systems impedance mismatch with the energy environment to the point that the drive stops moving and energy can no longer be converted. When it is safe to allow the system to move again, for instance when a wave is at a peak or trough and no vertically moving energy is available, the impedance can be decreased to provide power generation during the ensuing up or down wave motion. The electrical load impedance can be changed very rapidly as compared to the speed of the mechanical parts of the system.

The power generating or absorbing capacity of the generator and electronic circuits does not need to equal the power available to the natural energy converter during a storm. This would not be economical since the full power capacity would be used only rarely. The power capacity needs only to be sufficient to allow higher than optimum electric current to be drawn which increases the system impedance and hinders or essentially stops the energy converter from collecting natural power.

To provide intelligent control of the over-stroke protection technology, a sensor (e.g., shown as 80 in the drawing) is needed to detect the position of the stroking section of the energy converter. In the case of a rotary driven device such as a turbine, a sensor that measures speed is needed, for a linearly driven device, e.g., an hydraulic cylinder, a cylinder piston pivoting sensor is needed. Such sensors would normally be present in known power generating systems to provide operational information and, for use with the present invention, the outputs from such sensors are also communicated to the over-stroke controller. In a simple control strategy, an over-stroke control computer 22 constantly monitors the stroke position or system rotary speed and does not take action unless the measured values exceed a pre-selected value. When the stoke position

or rotary speed exceeds the pre-selected value, the over-stroke controller significantly increases the system impedance. If the next sensor readings are still too high, the impedance is again increased. This procedure is repeated until the sensor readings are within the acceptable range. If the rotary speed or position does not increase, the over-stroke control returns to the monitoring mode and the regular (known) power conversion circuit continues to operate the system.

A somewhat more sophisticated strategy for linear motion over-stroke or over-speed control requires calculating the rate of increase of stroke speed or rotary speed. This does not require a sensor in addition to the aforementioned sensors because the difference between sequential readings taken in fixed time steps indicates whether the system is speeding up or not. This speed calculation combined with the absolute position or speed allows the over-stroke control to chose larger or smaller increments of impedance increase to effect a smoother and more efficient control strategy. For example, if the stroke is approaching the allowable stroke limit but is not moving too fast, and is slowing down, a small amount of impedance increase is applied. This keeps the generator operating in an efficient range, and brings the system to a smooth stop. However, in an extreme condition, when the stroke is approaching the allowable stroke limit at a high rate of speed, and the speed is increasing, a large amount of impedance increase is applied. Also, the speed sensor is quickly checked again and the impedance increased again if necessary. This situation will produce inefficient power generation for a short period, and an abrupt braking of the stroke motion. However, power is still generated and the stroke is prevented from mechanically hitting its end-stop and damaging the system.

In the case of rotary motion and the use of the foregoing described more sophisticated control strategy, a larger impedance increase is added to the system

if the speed is increasing rapidly as it approaches the speed limit than is added if the speed is slowly increasing as it approached the speed limit.


The described over-stroke/over-speed control approach does not cause undue wear on the system since excess energy is absorbed electrically and not mechanically. Also, it does not absorb all of the excess natural energy but rather causes the natural energy converter to become inefficient and to transfer only a small portion of the excess energy to the drive system.

What is claimed is:

- 1. A method of operating a system for generating electrical power from a source of input energy occurring at variable rates including first rates at which the input energy can be safely captured at high energy conversion efficiencies and second rates in excess of the first rates and at which capture of the input energy at the high energy conversion efficiencies is likely to cause mechanical damage to the system, the method comprising collecting, with a power collecting mechanism, the input energy when present at said first rates and driving an electrical generator with said collected energy for generating and transferring electrical energy, to an electrical load, at a high input energy conversion efficiency corresponding to a first mechanical impedance presented to the power collecting mechanism and, in response to the input energy arriving at said second rates, varying the impedance of said load for increasing the output current from the generator for reducing the input energy conversion efficiently of the generator for increasing the mechanical impedance of the generator.
- 2. A method of operating a system for generating electrical power from a source of input energy arriving at variable rates comprising capturing the input energy with a mechanism for converting the input energy to mechanical energy for driving an electrical generator for generating and transferring electrical energy to an electrical load, and, when the input energy exceeds a preselected rate, varying the impedance of the load for increasing the current to the load for decreasing the energy conversion efficiency of the generator for increasing the mechanical impedance of the generator presented to the energy capturing mechanism.

Abstract of the Disclosure

Protection against damage caused by excessively high input energies, e.g., from ocean storms, is provided in energy converting systems by, in response to the detection of excessively high input energies, changing the electrical impedance of the electrical load to which power from an electrical generator is being delivered for increasing the generator output current for reducing the power converting efficiency of the generator. This increases the mechanical impedance presented by the generator to the source of input energy for reducing the motion producing effect of the input energy.



10.9

1	::	, page
	į,	Service.
2		立会
	3000	
2	4	d de
2	25.35	ź:
117111	Ľ	ż
à,	2	The state
3		
estern.	ť	
titin dinti	2	1,1111
titin dinti	ť	1,1111
milit with their diese	THE RIVER IS AS AS	Thirth Then Miles
min inni nuti dan inin	HILL SIME STAN IS AS AS	Third thirty this Mark
min inni nuti dan inin	THE RIVER IS AS AS	Third thirty this Mark

Please type a plus sign (+) inside this box Under the Paperwork Reduction Act of 1995, no persons a valid OMB control number.	Patent and Trademark Office	. US DE	PTC/SB/01 (ugh 9/30/00. CMB 065 PARTMENT OF COMM information unless it co	1-0032 T
DECLARATION FOR LITH ITY OR	Attorney Docket Number		OPT 32 U	
DECLARATION FOR UTILITY OR DESIGN	First Named Inventor		SMALSER, P	. J.
PATENT APPLICATION	COMPLETE IF KNOWN			
(37 CFR 1.63)	Application Number			
☑ Declaration ☐ Declaration Submitted OR Submitted after Initial	Filing Date	OCT	. 28, 1999	
	Group Art Unit			
with Initial Filing (surcharge Filing (37 CFR 1.16 (e)) required)	Examiner Name			

As a below named inventor, I hereby declare that:							
My residence, post office address, and citizenship are as stated below next to my name.							
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:							
PROTECTION A	RRANGEMEN	T FOR NATUR	AL ENERG	ξY			
POWER GENERATIONSYSTEMS							
the specification of which		e of the Invention)					
is attached hereto	* · · · ·	• • • • • • • • • • • • • • • • • • • •					
OR Mas filed on (MM/DD/YYYY	\			* N. baran ow lakaman I			
mas inou on (man) but it it	<u> </u>	as Unite	ed States Applicat	ion Number or PCT International			
Application Number	and w	as amended on (MM/DD/)	m	(if applicable).			
I hereby state that I have reviewed amended by any amendment speci	and understand the	contents of the above ider	ntified specification	n, including the claims, as			
• • •							
I acknowledge the duty to disclose	information which is	material to patentability as	defined in 37 CF	R 1.56.			
I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.							
Prior Foreign Application Number(s)	Country	Foreign Filing Date (MWDD/YYYY)	Priority Not Claimed	Certified Copy Attached?			
(tumber(s)		[macoriti]	HOL CIAIMES	YES NO			
				H			
Additional foreign application numbers are listed on a supplemental priority data sheet PTC/SB/02B attached hereto:							
I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.							
Application Number(s)	Filing Dat	e (MWDD/YYYY)					
60/105,990	10/28/	1998	numbe supple	onal provisional application ors are listed on a mental priority data sheet B/02B attached hereto.			
l	1						

[Page 1 of 2]
Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type o y	des sign (+) belds the best. Under the Paparnark Rode	P. L. L. Hiller And of 1888, no posses M.	Approved 9 Pedant and Trademork Office as are mainted to respend to a c	. U.S. Parago St.	pp. Carl (a)-dat pr of commence des when I emples
DEC			Design Pate	nt Appli	cation
			Region(t), or 300(t) of any PCT or of each of the chains of the the first puragraph of 35 U.S.C which become archable below		
	S. Perent Application Number		Parent Filing Date (MM/DQYYYY)	Parent	Patent Number applicable)
FT Administra	U.S. or PCT bitamational ass				
	enter, I harply appoint the ful	uning Hydriania practicing	n a majatemental priority data a rità la prespeció dels application		ellushed harets.
		Optional Municipal Control of Con	a) namehadistisis number lid	M 3000	meer for Code
	Name	Registration	None		Region of the Market
				,	
	instituted prositionarial home		nd Provilleget Information stre	4 770/18/04C m	
Direct all care	rependence to: Cud	er Code Label	OR	Correspond	ense sidress below
Name	Michael	Y Eps	Lein	<u> روا المحادم میں جو س</u> ے ، جو میں	
Address	359 G	risgstown	RI		
Addition	0 11 200		ns ns		°502
Country	Belle M		08) 359-8453	70 (908)	
I havely death	re that of statements made t	ands of the own translate	a man from and that all abelian	mp made on little a statements on	median and being are the the so made are the the validy of the
panishmith by spokester or	fine or impringement, or but any palent intend thereon.	i, weder 18 U.S.C. 1991 a	ed that mak rather false state	nents May journ	the the vehilly of the
Name of \$	Firet laventor:		A petition has been	Ried for this und	grad iterator
	tren times first and midd	M smh		Name or Burns	!!
Pa	ul J		Smal.	ser.	· iola7/११
Mandan	X fant	y, Lua	Courty US	A	UJB
Rushdonate	Hamilton :		A		
Post Office		aple Shad	1100		
Post Office /		ns	08690	Country	USA
Car IT at	milton Square	-1		طعنك سبب	VO2A stacked here!

احواثم مسمير	o pina algo (+) inside ante buz	→ □	Atamust	PT0/08/01 (124
	Under the Paperwork Re a voild CMB central Paper	Mindlen Àid of 1886, no pare dor.	Approved Palent and Tredemers Off one are inquired to respend to a	TAL DEPARTMENT OF COMMEN
DE				
	SCALOR IION	- Ounty o	r Design Pate	nt Application
United States United States	of America, inted below an	120 of any United States up d, incolor as the subject me	eduction(s), or 300(s) of any PC Bor of each of the states of an	international application designating the
information wanted the nation	rhish is material to personabilities red or PGT international filtre	by an defined in 37 CFR 1.8 deleted this sentiments	y the first paragraph of 35 U.S.C 5 which become available below	I international application designating in equivaries in set discharge in the pri 112.1 generalisation the old in the pri and the filling date of the prior application
U		'	Parent Filing Date	Parent Patent Number
	Mumbe		(MM/DD/YYY)	# applicable
-				
As a comment in	i U.S. or PGY Interruptional ap- vector, I haraby associat the S	ploution numbers are lated :		heat PTC/05/000 allashed hereto.
and Trademak	Ciller servested thermalik:	Outsmar Humber	rich to prospecte this application	and to transport of transports in the Pate
		D Registered grantfirmers) Agunahaghdration mumber list	Abridar Code
	Nane	Registration Alember	Numo	Anglet dan
Mic	had Y	21186		
	Epstein	2/180		
Addiend		ed on suspinmental Residen	ed Prestilings information shoe	PTOYNEGEC standard better
Direct all com	The second secon	Somer Number lar Code Label	OR D	
Name	Michae		7	To continue and the board
Address			stein	
Addition		Grisgstou	n Pd	
City	Belle Mi	ead	1200	
Courdry	UJA		8 359-8453	08502
I hereby dealer			are tree and that of statement the brendings that willed false	19081359-1483
physical at a	My pulses interest thereign,	. under 18 U.S.C. 1001 and	The brandadge that willful folia: I that much willful folia: stateme	statements and the the us made are one may jesperate the validly of the
Name of 2	2 nd Inventor:			ed for this unalgood inventor
	en Hara that and midd	o Sf anyl)		
Cha			Carroll	eme or humana
hrvadar's Ngrabas		s B. Carroll	Carroll	1 100
Parkings (I	Trenton			10/27/89
Post Office Ad		ialston		USA
		013) CN	Dr.	
Post Office Ad				
City December 1	Trenton	nj =		county USA
	inventors are being name:	en the supplement	al Additional Inventor(a) she	et(e) PTO/EB/02A stacked kerelo